



Photometrics

Flux out: 99 lm

		\land		
3 ft / 1 m	265 / 390 fc		0.65 ft	
	2,853 / 4,206 lx		19.88 cm	
7 ft / 2 m	66 / 97 fc		1.30 ft	
	713 / 1,051 lx		39.75 cm	
10 ft / 3 m	29 / 43 fc		1.95 ft	
	316 / 467 lx		59.63 cm	
	16 / 24 fc		2.61 ft	
13 ft / 4 m	178 / 262 lx		79.50 cm	
16 ft / 5 m	10 / 15 fc		3.26 ft	
	114 / 168 lx		99.38 cm	
	7/11 £-			
20 ft / 6 m	7 / 11 fc 79 / 116 lx		3.91 ft 119.26 cm	
	777 I TO IX		119.20 CM	
00 6 / 7	5 / 7 fc		4.56 ft	
23 ft / 7 m	58 / 85 lx		139.13 cm	
26 ft / 8 m	4 / 6 fc		5.21 ft	
	44 / 65 lx		159.01 cm	
30 ft / 9 m	3 / 4 fc		5.87 ft	
	35 / 51 lx		178.88 cm	
33 ft / 10 m	0 () (
	2 / 3 fc 28 / 42 lx		6.52 ft	
	20 / 42 IX		198.76 cm	
Height	E avg / E max	Angle: 10°	Diameter	
Note: the Curves indicate the illuminated area and the				

Note: the Curves indicate the illuminated area and the average illumination when the luminaire is at different distance



WEBSITE:www.prolights.it

MAIL: support@prolights.it





Photometrics

	Flux out: 24 lm			
		\bigwedge		
3 ft / 1 m	65 / 92 fc		0.67 ft	
	703 / 1,000 lx		20.53 cm	
7 ft / 2 m	16 / 23 fc		1.35 ft	
	1757250 IX		41.06 cm	
10 년 / 2	7 / 10 fc		2.02 ft	
10 ft / 3 m	707 1111X		61.59 cm	
13 ft / 4 m	4 / 5 fc		2.69 ft	
	43 / 62 lx		82.11 cm	
16 ft / 5 m	2/3 fc		3.37 ft	
	28 / 40 lx 1 / 2 fc		102.64 cm 4.04 ft	
20 ft / 6 m	19/27 lx		123.17 cm	
23 ft / 7 m	1.33 / 1.89 fc 14 / 20 lx		4.71 ft	
20107711			143.70 cm	
26 ft / 8 m	1 / 1.45 fc 11 / 15 lx		5.38 ft	
	0.80 / 1.14 fc		164.23 cm 6.06 ft	
30 ft / 9 m	8 / 12 lx		184.76 cm	
Height	E avg / E max	Angle: 10°	Diameter	
	Note	: the Curves indicate the illuminated a	rea and the	
average illumination when the luminaire is at different distance				

. . . .



WEBSITE:www.prolights.it

MAIL: support@prolights.it



Portable and cable free accent battery light



Photometrics

Flux out: 35 lm 3 ft / 1 m 95 / 140 fc 1,032 / 1,517 lx 0.64 ft 19.61 cm 7 ft / 2 m 23 / 35 fc 258 / 379 lx 1.28 ft 39.22 cm 10 ft / 3 m 10 / 15 fc 114 / 168 lx 1.93 ft 58.83 cm 5/8 fc 2.57 ft 13 ft / 4 m 64 / 94 lx 78.45 cm 16 ft / 5 m 3 / 5 fc 41 / 60 lx 3.22 ft 98.06 cm 20 ft / 6 m 2 / 3 fc 28 / 42 lx 3.86 ft 117.67 cm 23 ft / 7 m 1 / 2.87 fc 21 / 30 lx 4.50 ft 137.28 cm 1.49 / 2.20 fc 5.15 ft 26 ft / 8 m 16 / 23 lx 156.89 cm 1.18 / 1.74 fc 5.79 ft 30 ft / 9 m 12 / 18 lx 176.50 cm Angle: 10° Height E avg / E max Diameter Note: the Curves indicate the illuminated area and the average illumination when the luminaire is at different distance

WEBSITE:www.prolights.it

MAIL: support@prolights.it





Photometrics

	Flux out: 5 lm				
		\land			
3 ft / 1 m	15 / 22 fc		0.63 ft		
	172 / 241 lx		19.21 cm		
7 ft / 2 m	3 / 5 fc		1.26 ft		
	42 / 60 lx		38.41 cm		
10 (1 / 2	1 / 2 fc		1.89 ft		
10 ft / 3 m	19 / 26 lx		57.62 cm		
	1 / 0.47 fc		2.52 ft		
13 ft / 4 m	10 / 15 lx		76.83 cm		
	0.64 / 0.89 fc		3.15 ft		
16 ft / 5 m	6 / 9 lx		96.04 cm		
20 ft / 6 m	0.44 / 0.62 fc		3.78 ft		
20 ft / 6 m	4 / 6 lx		115.24 cm		
23 ft / 7 m	0.33 / 0.46 fc		4.41 ft		
23 IL / 7 III	374 IX		134.45 cm		
26 ft / 8 m	0.25 / 0.35 fc		5.04 ft		
2011/011			153.66 cm		
30 ft / 9 m	0.19 / 0.28 fc		5.67 ft		
	2721x		172.87 cm		
Height	E avg / E max	Angle: 10°	Diameter		
Note: the Curves indicate the illuminated area and the					
average illumination when the luminaire is at different distance					

_ . . .



WEBSITE:www.prolights.it

MAIL: support@prolights.it

DotQ - White

Portable and cable free accent battery light



Photometrics

Flux out: 38 lm

		\bigwedge			
3 ft / 1 m	104 / 152 fc		0.65 ft		
	1,120 / 1,646 lx		19.88 cm		
76.40	26 / 38 fc		1.30 ft		
7 ft / 2 m	20074111		39.75 cm		
10 6 / 0	11 / 16 fc		1.95 ft		
10 ft / 3 m	124 / 182 lx		59.63 cm		
40 6 / 4	6 / 9 fc		2.61 ft		
13 ft / 4 m	44 / 65 lx		79.50 cm		
16 ft / 5 m	4/ 6 fc		3.26 ft		
	44 / 65 lx		99.38 cm		
20 ft / 6 m	2 / 4 fc		3.91 ft		
20π/6m	31 / 45 lx		119.26 cm		
22 4 / 7 m	2 / 3 fc		4.56 ft		
23 ft / 7 m	22 / 33 lx		139.13 cm		
26 ft / 8 m	1.62 / 2 fc		5.21 ft		
26 π / 8 m	1772318		159.01 cm		
30 ft / 9 m	1.28 / 1.88 fc		5.87 ft		
	13 / 20 lx		178.88 cm		
Height	E avg / E max	Angle: 10°	Diameter		
Note: the Curves indicate the illuminated area and the					
average illumination when the luminaire is at different distance					

WEBSITE:www.prolights.it

MAIL: support@prolights.it